



FACILITY	POST HEIGHT	POST DIAMETER	TOP DIAMETER	POST DEPTH BELOW GROUND LEVEL	FOOTING SIZE
Local	8m/5m	80mm/80mm	50mm/50mm	0.7m/0.6m	1.05m x 0.45d / 0.9m x 0.45d
Regional	10m/6.5m	112mm/80mm	70mm/50mm	0.8m/0.7m	1.2m x 0.45d / 1.05m x 0.45d
State League	12m/8m	112mm/80mm	70mm/50mm	0.9m/0.7m	1.35m x 0.45d / 1.05m x 0.45d

- NOTES
1. REGIONAL FACILITIES : LAJAMANU, YUENDUMU, TI TREE
 2. LOCAL FACILITIES : OTHER OVALS IN COUNCIL REGION
 3. CONCRETE GRADE FOR FOOTING 25 MPA
 4. POINT POSTS ARE PREFERABLY 2/3 THE HEIGHT OF GOAL POSTS
 5. PADDING ON ALL POSTS - 2.5M FROM GROUND TO TOP; 35MM THICK FOAM COVERED IN CANVAS OR PAINTED.
 6. INTERCHANGE BENCHES FORM PART OF BOUNDARY FENCE
 7. LOCATE INTERCHANGE BENCHES ON WESTERN SIDE (FACING AWAY FROM SUN)